

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name: K-FLEX K- 414**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

- **Product category** PC1 Adhesives, sealants
- **Application of the substance / the mixture** Adhesives

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

L'isolante K-FLEX S.p.A.  
via Don Locatelli, 35 20877 Roncello (MB) ITALY  
Tel. +39 039 6824.1  
e-mail: Kflex-Reach@isolante.com

· **Further information obtainable from: R&D Dept.**

· **1.4 Emergency telephone number:**

Tel. +39 039 6824.1 (9.00-17.00)

ITALIA Centro Antiveleeni Ospedale Niguarda "Ca' Granda" MILANO tel. 02/66101029; Fondazione Maugeri - Clinica del lavoro e della Riabilitazione PAVIA tel. 0382/24444; Centro Documentazione Tossicologica - Università degli Studi PADOVA tel. 049/8275078; Centro Antiveleeni Istituto Scientifico "G. Gaslini" GENOVA tel. 010/5636245; Centro Antiveleeni Azienda Ospedaliera "Careggi" FIRENZE tel. 055/4277328; Centro Antiveleeni "Policlinico Gemelli" ROMA tel. 06/3054343; Centro Antiveleeni Università degli Studi di Roma "La Sapienza" ROMA tel. 06/49970698; Centro Antiveleeni Azienda Ospedaliera "A. Cardarelli" NAPOLI tel. 081/7472870; Centro antiveleeni Azienda Ospedaliera Universitaria FOGGIA tel. 0881/731111

AUSTRIA Vergiftungsinformationszentrale +43 1 406 43 43

BELGIUM Centre Antipoisons-Antigifcentrum +32 30245245

BULGARIA National Toxicology Centre at National Clinical Toxicology Centre +359 2 9154 233

CROATIA Poison Control Centre Zagreb +385 1 2348342

CECH REPUBLIC Toxicological Information Centre + 420224919 293

DENMARK Poison Information Centre n +45 82 12 12 12

ESTONIA Estonian Poison Information centre +372 626 93 90

FINLAND Finnish Poison Information Centre +358 9 471977

FRANCE Centre Antipoison et de Toxicovigilance de Angers +33 2 41 35 33 30

HUNGARY Health Toxicology Information Service +36 80 20 11 99

IRELAND Poison Information Centre of Ireland +353 1 809 2166

LATVIA Valsts Toksikologijas centres + 371 67042473

LITHUANIA Lithuania Poison Control and Information Bureau +370 5 236 20 52

NORGE Giftinformasjonen : 22 59 13 00 (døgnåpen)

PORTUGAL CIAV Centro de Informacao Antivenenos +351 808 250 143

SLOVAKIA National Toxicological Information Center +421 2 54 774 166

POLAND Informacja toksykologiczna w Polsce +48 42 631 47 24 (czynna 7:00-15:00)

SPAIN Instituto Nacional de Toxicologia +34 156 20420

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2      H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

**Trade name: K-FLEX K- 414**

(Contd. of page 1)



GHS07

Skin Irrit. 2      H315 Causes skin irritation.  
 Eye Irrit. 2      H319 Causes serious eye irritation.  
 STOT SE 3      H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02    GHS07    GHS09

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

Solvent naphtha (petroleum), hydrotreated light naphthenic; Hydrocarbons C6-C7 isoalkanes cyclics < 5% n-hexane (REACH Registered Name)

· **Hazard statements**

H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P233                    Keep container tightly closed.  
 P261                    Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P280                    Wear protective gloves/protective clothing/eye protection/face protection.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+P340            IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312                    Call a POISON CENTER/doctor if you feel unwell.  
 P321                    Specific treatment (see on this label).  
 P362+P364            Take off contaminated clothing and wash it before reuse.  
 P403+P233            Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235            Store in a well-ventilated place. Keep cool.  
 P405                    Store locked up.  
 P501                    Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Contains Rosin. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

**Trade name: K-FLEX K- 414**

(Contd. of page 2)

· <b>Dangerous components:</b>		
CAS: 92062-15-2 EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Solvent naphtha (petroleum), hydrotreated light naphthenic; Hydrocarbons C6-C7 isoalkanes cyclics < 5% n-hexane (REACH Registered Name) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	30-50%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	15-25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-15%
CAS: 64742-49-0 EC number: 931-254-9 Reg.nr.: 01-2119484651-34	Naphtha (petroleum), hydrotreated light; hydrocarbons C6 isoalkanes < 5% n-hexane (REACH Registered Name) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-15%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32	Rosin Skin Sens. 1, H317	0.1-0.5%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119555270-46	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	0.05-0.2%
CAS: 1330-20-7 EINECS: 215-535-7	xylene (mix) Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	0.05-0.2%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	0.05-0.2%

· **UVCB (Unknown Variable Complex reaction product or Biological Origin)**

64742-49-0	Naphtha (petroleum), hydrotreated light; hydrocarbons C6 isoalkanes < 5% n-hexane (REACH Registered Name)
------------	--

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures**· **4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**· **5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**

Water

Water with full jet

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

Trade name: **K-FLEX K- 414**

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store outdoors.  
Store the product in well areated local at a temperature between 5 and 35°C. Avoid temperature up 40°C and below 5°C because the product could freeze and coagulate becoming unusable.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**141-78-6 Ethyl acetate**

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

**67-64-1 Acetone**

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-----	--

**8050-09-7 Rosin**

WEL	Short-term value: 0.15 mg/m <sup>3</sup> Long-term value: 0.05 mg/m <sup>3</sup> Sen
-----	--

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

**Trade name: K-FLEX K- 414**

(Contd. of page 4)

**1330-20-7 xylene (mix)**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

**100-41-4 ethylbenzene**

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

**· DNELs****141-78-6 Ethyl acetate**

Dermal	Long term-Systemic effect	63 mg/kg (workers)
Inhalative	Long term-Systemic effect	1,468 mg/m <sup>3</sup> (workers)
	Long term-Local effect	1,468 mg/m <sup>3</sup> (workers)

**67-64-1 Acetone**

Dermal	Long term-Systemic effect	186 mg/kg (workers)
Inhalative	Long term-Local effect	2,420 mg/m <sup>3</sup> (workers)

**64742-49-0 Naphtha (petroleum), hydrotreated light; hydrocarbons C6 isoalkanes < 5% n-hexane (REACH Registered Name)**

Dermal	Long term-Systemic effect	13,964 mg/kg (workers)
Inhalative	Long term-Local effect	5,306 mg/m <sup>3</sup> (workers)

**· PNECs****141-78-6 Ethyl acetate**

fresh water	0.26 mg/l (frs)
	0.26 mg/l (water)
marine water	26 mg/l (mar)
	26 mg/l (water)
Intermittent release	650 mg/l (water)

**67-64-1 Acetone**

fresh water	10.6 mg/l (water)
marine water	1.06 mg/l (water)
Intermittent release	21 mg/l (water)
sediment-marine water	3.04 mg/l (water)
sediment-fresh water	30.4 mg/l (water)
sewage treatment plant	100 mg/l (water)
Soil	29.5 mg/kg (soil)

**· Ingredients with biological limit values:****1330-20-7 xylene (mix)**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

**Trade name: K-FLEX K- 414**

(Contd. of page 5)

- Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** Filter A/P2
  - **Protection of hands:**



Protective gloves

- Rubber gloves
- **Material of gloves** Butyl rubber, BR
  - **Penetration time of glove material**  
For the mixture of chemicals mentioned below the penetration time has to be at least 240 minutes (Permeation according to EN 374 Part 3: Level 5).  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - **Eye protection:**



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

· <b>Form:</b>	Fluid
· <b>Colour:</b>	Orange
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

##### · Change in condition

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	36 °C

· **Flash point:** -20 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** >200 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### · Explosion limits:

· <b>Lower:</b>	1.2 Vol %
· <b>Upper:</b>	13 Vol %

· **Vapour pressure at 20 °C:** 233 hPa

· <b>Density at 20 °C:</b>	0.85 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

Trade name: K-FLEX K- 414

(Contd. of page 6)

· <b>Solubility in / Miscibility with water:</b>	Soluble.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C:</b>	700 mPas
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	78.0 %
<b>VOC (EU):</b>	663.0 g/l
· <b>Solids content:</b>	22.0 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**141-78-6 Ethyl acetate**

Oral	LD50	4,935 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (rat)

**67-64-1 Acetone**

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

**128-37-0 Butylated hydroxytoluene**

Oral	LD50	890 mg/kg (rat)
------	------	-----------------

**1330-20-7 xylene (mix)**

Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	6,350 mg/l (rat)

**100-41-4 ethylbenzene**

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

Trade name: K-FLEX K- 414

(Contd. of page 7)

- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

##### 141-78-6 Ethyl acetate

EC50/48h	165,000 µg/l (daphnia magna)
----------	------------------------------

##### 67-64-1 Acetone

EC50/48h	8,800,000 µg/l (daphnia magna)
----------	--------------------------------

### · 12.2 Persistence and degradability

 No further relevant information available.

### · 12.3 Bioaccumulative potential

#### 141-78-6 Ethyl acetate

LogPow	30
--------	----

#### 64742-49-0 Naphtha (petroleum), hydrotreated light; hydrocarbons C6 isoalkanes < 5% n-hexane (REACH Registered Name)

LogPow	3.6
--------	-----

### · 12.4 Mobility in soil

 No further relevant information available.

### · Ecotoxicological effects:

· **Remark:** Toxic for fish

### · Additional ecological information:

#### · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

### · 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### · 12.6 Other adverse effects

 No further relevant information available.

## SECTION 13: Disposal considerations

### · 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018




Version number 15

Revision: 12.07.2018

Trade name: K-FLEX K- 414

(Contd. of page 8)

### SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1133
· 14.2 UN proper shipping name · ADR · IMDG  · IATA	1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS ADHESIVES (Solvent naphtha (petroleum), hydrotreated light naphthenic; Hydrocarbons C6-C7 isoalkanes cyclics < 5% n-hexane (REACH Registered Name), HEXANES), MARINE POLLUTANT  ADHESIVES
· 14.3 Transport hazard class(es) · ADR, IMDG	
 	
· Class · Label	3 Flammable liquids. 3
· IATA	
	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Butylated hydroxytoluene, Solvent naphtha (petroleum), hydrotreated light naphthenic; Hydrocarbons C6-C7 isoalkanes cyclics < 5% n-hexane (REACH Registered Name)
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids. - F-E,S-D A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 E

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31 and 830/2015

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

Trade name: K-FLEX K- 414

(Contd. of page 9)

· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 40

#### · National regulations:

#### · Technical instructions (air):

Class	Share in %
NK	78.0

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

#### · Department issuing SDS: R&D Dept.

#### · Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31 and 830/2015**

Printing date 12.07.2018

Version number 15

Revision: 12.07.2018

**Trade name: K-FLEX K- 414**

(Contd. of page 10)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **\* Data compared to the previous version altered.**

GB