

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: K-FLEX SPECIAL THINNER

Chemical name and synonym: THINNER FOR ADHESIVES

1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended use: Thinner for adhesives recommended for professional use only. Retail sale and use is prohibited.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

L'Isolante K-FLEX S.p.A.

via Don Locatelli, 35 20877 Roncello (MB) ITALY

Tel. +39 039 6824.1

e-mail: Kflex-Reach@kflex.com

Further information obtainable from: R&D Dept.

1.4 Emergency telephone number:

Tel. +39 039 6824.1 (9.00-17.00)

Centro Antiveleni Milano 02-66101029 (CAV Ospedale Niguarda Ca'Granda -Milano) (h24)

Centro Antiveleni Pavia 0382-24444 (CAV IRCCS Fondazione Maugeri-Pavia)

Centro Antiveleni di Bergamo 800883300 (CAV Ospedali Riuniti-Bergamo)

Centro Antiveleni di Firenze 055-7947819 (CAV Ospedale Careggi- Firenze)

Centro Antiveleni di Roma 06-3054343 (CAV Policlinico Gemelli-Roma)

Centro Antiveleni di Roma 06-49978000 (CAV Policlinico Umberto I - Roma)

Centro Antiveleni di Napoli 081-7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour
Eye irritation, category 2	H319	Causes serious eye irritation
Specific target organ toxicity – single exposure, category 3	H336	May causes drowsiness or dizziness
Hazardous to the aquatic environment, Chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

K-FLEX SPECIAL THINNER
Page n. 1 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

Hazard pictograms:



Signal word: Danger

Hazard statements:

- H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves / protective clothing / eye protection / face protection.
P370+P378 In case of fire:use carbon dioxide, foam, chemical powder. Do not use water.
P273 Avoid release to the environment.

Contains: ACETONE
ETHYL ACETATE
HEPTANE

2.3 Other hazards

On the basis of available data, the products does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Contains:

Identification	x=Conc.%	Classification 1272/2008 (CLP)
ETHYL ACETATE CAS 141-78-6 CE 205-500-4 INDEX 607-022-00-5 Nr. Reg. 01-2119475103-46	30 ≤ x < 60	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
ACETONE CAS 67-64-1 EC 200-662-2 INDEX 606-001-00-8 Reg. no. 01-2119471330-49	30 ≤ x < 60	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

K-FLEX SPECIAL THINNER
Page n. 2 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

HEPTANE
CAS 142-82-5

5 ≤ x < 10 Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315,
STOT SE 3

H336, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1, Classification
note according to Annex VI to the CLP Regulation:C

EC 205-563-8
INDEX 601-008-00-2
Reg. no. 01-2119475515-33

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4: First aid measures

4.1 Description of first aid measures

EYES: Remove contact lenses, if present Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3 Indication of any immediate medical attention and special treatment needed

Information not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2 Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products..

5.3 Advice for firefighters

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS.

K-FLEX SPECIAL THINNER
Page n. 3 of 19

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2 Environmental precautions:

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3 Methods and material for containment and cleaning up:

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters.

Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2 Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3 Specific end use(s)

Information not available.

Safety data sheet
According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Regulatory References:

CZE	Česká Republika	Nariadení vlády č. 246/2018 Sb. Nariadení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LIMITES DE EXPOSICION PROFESIONAL PARA AGENTES QUIMICOS EN ESPANA 2019(INSST)
FIN	Suomi	HTP-VÄRDEN 2018. Koncentrationer som befunnits skadliga. SOCIAL-OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 10/2018
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition published 2018)
GRC	Ελλάδα	ΕΠΗΜΕΡΙΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM-SZCSM együttes rendelet módosításáról
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
ROU	România	HOTĂRĂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SWE	Sverige	Hygieniska gränsvärden. AFS 2018:1
EU	OEL EU	Direttiva (UE) 2017/2398; Direttiva (UE) 2017/164; Direttiva 2009/161/UE; Direttiva 2006/15/CE; Direttiva 2004/37/CE; Direttiva 2000/39/CE; Direttiva 91/322/CEE.
	TLV-ACGIH	ACGIH 2019

ETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks/Observations
TLV	CZE	700	194,6	900	250,2	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
VLA	ESP	734	200	1468	400	
HTP	FIN	730	200	1470	400	
VLEP	FRA	1400	400			
WEL	GBR	734	200	1468	400	
TLV	GRC	734	200	1468	400	
GVI/KGVI	HRV	734	200	1468	400	
AK	HUN	734		1468		
VLEP	ITA	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	400	111	500	139	
NGV/KGV	SWE	550	150	1100	300	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Predicted no-effect concentration - PNEC
Normal value in fresh water

0,24 mg/l

Normal value in marine water

0,02 mg/l

Normal value for fresh water sediment

1,15 mg/kg/d

Normal value for marine water sediment

0,115 mg/kg/d

Safety data sheet
According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

Normal value of STP microorganisms	650	mg/l
Normal value for the food chain (secondary poisoning)	0,2	g/kg
Normal value for the terrestrial compartment	0,148	mg/kg/d

Health – Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic 4,5 mg/kg bw/d	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral								
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/kg
Skin				37 mg/kg bw/d				63 mg/kg bw/d

ACETONE
Threshold Limit Value
Type

	Country	TWA/8h		STEL/15min	Remarks/Observations
	mg/m3	ppm	mg/m3	ppm	
TLV	CZE	800	336,8	1500	631,5
AGW	DEU	1200	500	2400 (C)	1000 (C)
MAK	DEU	1200	500	2400	1000
HTP	FIN	1200	500	1500	630
VLEP	FRA	1210	500	2420	1000
WEL	GBR	1210	500	3620	1500
TLV	GRC	1780		3560	
GVI/KGVI	HRV	1210	500		
AK	HUN	1210			
VLEP	ITA	1210	500		
NDS/NDSch	POL	600		1800	
TLV ROU		1210	500		
NGV/KGV	SWE	600	250	1200 (C)	500 (C)
OEL EU		1210	500		
TLV-ACGIH			250		500

Predicted no-effect concentration - PNEC
Normal value in fresh water

10,6 mg/l

K-FLEX SPECIAL THINNER
Page n. 6 of 17

Safety data sheet
According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

Normal value in marine water	21	mg/l
Normal value for fresh water sediment	30,4	mg/kg
Normal value for marine water sediment	3,04	mg/kg
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	33,3	mg/kg

Health – Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				62 mg/kg				
Inhalation				200 mg/m ³		2420 mg/m ³		1210 mg/m ³
Skin				62 mg/kg				186 mg/kg

HEPTANE
Threshold limit value
Type

Country	TWA/8h	STEL/15min	Remarks/Observations
	mg/m ³	ppm	
TLV	CZE 1000	244	
MAK	DEU 2100	500	
VLA	ESP 2085	500	Como n-Eptano
VLEP	FRA 1668	400	
WEL	GBR 2085	500	
TLV	GRC 2000	500	
GVI/KGVI	HRV 2085	500	SKIN
AK	HUN 2000		
VLEP	ITA 2085	500	
NDS/NDSch	POL 1200		
TLV	ROU 2085	500	
NGV/KGV	SWE 800	200	
OEL	EU 2085	500	
TLV-ACGIH		400	
		2049	
		500	

Health – Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				149 mg/kg Bw/d				
Inhalation				447 mg/m ³				2085 mg/m ³
Skin				149 mg/kg bw/d				300 mg/kg bw/d

K-FLEX SPECIAL THINNER
Page n. 7 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND= hazard identified but no DNEL/PNEC available; NEA= no exposure expected; NPI= no hazard identified

8.2 Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards. Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing. Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties.

K-FLEX SPECIAL THINNER
Page n. 8 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

Appearance	liquid
Colour	transparent
Odour	characteristic of solvent
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	55 °C.
Boiling range.	Not available.
Flash point.	-18 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	1,2 % (V/V).
Upper inflammability limit.	13 % (V/V).
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	127,05 mmHg
Vapour density	Not available.
Relative density.	0,75
Solubility	immiscible with water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information.	
Molecular weight.	76,094
VOC (Directive 1999/13/EC) :	100,00 % - 750,00 g/litre.
VOC (volatile carbon) :	60,69 % - 455,15 g/litre.

SECTION 10: Stability and reactivity

10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.
ETHYL ACETATE: decomposes slowly into acetic acid and ethanol under the effect of light, air and water.
ACETONE: decomposes under the effect of heat.

10.2 Chemical stability

The product is stable in normal conditions of use and storage.

10.3 Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

K-FLEX SPECIAL THINNER
Page n. 9 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

ETHYL ACETATE: risk of explosion on contact with: metals, alkalis, hydrides. oleum. May react violently with: fluoride, strong oxidising agents, chlorosulfuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

ACETONE: risk of explosion on contact with: bromine trifluoride, difluoro dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl chloride, chromosulphuric acid, fluorine, strong oxidising agents. Develops flammable gas on contact with: nitrosyl perchlorate.

10.4 Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHYL ACETATE: avoid exposure to light, sources of heat and naked flames.

ACETONE: avoid exposure to sources of heat, naked flames.

10.5 Incompatible materials:

ETHYL ACETATE: incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

ACETONE: Incompatible with: acids, oxidising substances.

10.6 Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ACETONE: may develop: ketenes, irritant substances.

SECTION 11: Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1 Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

K-FLEX SPECIAL THINNER
Page n. 10 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

HEPTANE

LD50 (Oral) > 8 mg/kg bw Ratto

LD50 (Dermal) > 20000 mg/kg-bw Coniglio LC50 (Inhalation) > 23,3 mg/l/4h Ratto

ACETONE

LD50 (Oral) 5800 mg/kg ratto LD50 (Dermal) > 20 ml/kg coniglio

LC50 (Inhalation) 21,09 ppm/8h ratto

ETHYL ACETATE

LD50 (Oral) 4934 mg/kg dw ratto

LD50 (Dermal) > 20000 mg/kg-bw coniglio

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12: Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

HEPTANE

LC50 - for Fish

> 13,4 mg/l/96h *Oncorhynchus mykiss*

EC50 - for Crustacea

3,2 mg/l/48h *Daphnia magna*

K-FLEX SPECIAL THINNER
Page n. 11 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

EC50 - for Algae / Aquatic Plants	12 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Crustacea	2,4 mg/l Daphnia pulex
Chronic NOEC for Algae / Aquatic Plants	> 100 mg/l Scenedesmus subspicatus

ACETONE	
LC50 - for Fish	8120 mg/l/96h Pimephales promelas
EC50 - for Crustacea	8800 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	530 mg/l/72h Alga

ETHYL ACETATE	
LC50 - for Fish	230 mg/l/96h Pimephales promelas
EC50 - for Crustacea	165 mg/l/48h Daphnia magna
Chronic NOEC for Crustacea	2,4 mg/l Daphnia pulex
Chronic NOEC for Algae / Aquatic Plants	> 100 mg/l Scenedesmus subspicatus

12.2 Persistence and degradability

The paraffinic hydrocarbons fraction may be considered biodegradable in water and in air. They distribute mostly in the air. They distribute mostly in the air. The small non biodegradable amount which spreads into water tends to accumulate in fish.

HEPTANE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

ACETONE	
Rapidly degradable	

ETHYL ACETATE	
Solubility in water	> 10000 mg/l
Rapidly degradable	

12.3 Bioaccumulative potential

HEPTANE	
Partition coefficient: n-octanol/water	4,5
BCF	552

ACETONE	
Partition coefficient: n-octanol/water	-0,23
BCF	3

K-FLEX SPECIAL THINNER
Page n. 12 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

ETHYL ACETATE
Partition coefficient: n-octanol/water 0,68
BCF 30

12.4 Mobility in soil

HEPTANE
Partition coefficient: soil/water 2,38

12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6 Other adverse effects

Information not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA: 1993

14.2 UN proper shipping name

ADR/RID: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; ACETONE)

IMDG: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; ACETONE; HEPTANE)

IATA: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; ACETONE)

14.3 Transport hazard class(es)

ADR/RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



K-FLEX SPECIAL THINNER
Page n. 13 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

14.4 Packing group

ADR/RID, IMDG, IATA: II

14.5 Environmental hazards

ADR/RID: Environmentally

Hazardous



IMDG: Marine Pollutant



IATA: NO

For air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6 Special precautions for user

ADR/RID:	HIN-Kemler:33	Limited Quantities: 1L	Tunnel restriction code: (D/E)
	Special Provision: 640C		
IMDG:	EMS: F-E, S-E	Limited Quantities: 1L	
IATA:	Cargo:	Maximum quantity: 60L	Packaging instructions: 364
	Pass:	Maximum quantity: 5L	Packaging instructions: 353
	Special Instructions:	A3	

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category – Directive 2012/18/EC:P5c-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product
Point 3 - 40

Substances in Candidate List (Art.59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
NoneSubstances subject to exportation reporting pursuant to (EC) Reg. 649/2012:
NoneSubstances subject to the Rotterdam Convention:
NoneK-FLEX SPECIAL THINNER
Page n. 14 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

Substances subject to the Stockholm Convention:
None

Healthcare controls:

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2 Chemical safety assessment:

A chemical safety assessment has been performed for the following contained substances.

SECTION 16: Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%

K-FLEX SPECIAL THINNER
Page n. 15 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1.Regulation (EC) 1907/2006 (REACH) of the European Parliament
 - 2.Regulation (EC) 1272/2008 (CLP) of the European Parliament
 - 3.Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 - 4.Regulation (EU) 2015/830 of the European Parliament
 - 5.Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 - 6.Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 - 7.Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 - 8.Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 - 9.Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 - 10.Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 - 11.Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 - 12.Regulation (EU) 2016/1179 (IX Atp. CLP)
 - 13.Regulation (EU) 2017/776 (X Atp. CLP)
 - 14.Regulation (EU) 2018/669 (XI Atp. CLP)
 - 15.Regulation (EU) 2018/1480 (XIII Atp. CLP)
 - 16.Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità)
 - Italy Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

K-FLEX SPECIAL THINNER
Page n. 16 of 17

Safety data sheet

According to Annex II to REACH – Regulation 2015/830

K-FLEX SPECIAL THINNER

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP

Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.